

# IWO-6950-MATX

## 15" TFT Industrial Panel PC

### Specification

- € **Designed for industrial Panel PC mountable**
- € **Designed by steel made front panel meet NEMA4 (IP65) / NEMA12 (IP52) (Optional)**
- € **Processor:** Socket 478 for Intel® Pentium® 4 (FSB 400/533 MHz) supports Hyper Threading Technology (3.0). Socket 370 for Intel® Pentium® 3/Celeron/Tualatin for option.
- € **Micro-ATX / Baby-AT size motherboard**
- € **Four PCI / ISA full length slots for expansion**
- € **15.0" TFT LCD Display:**
  - ò 1024x768 (XGA) resolutions
  - ò 250 cd/m<sup>2</sup> brightness
  - ò 50000 hours LCD MTBF
  - ò 50000 hours backlight lifetime
- € **System Memory:**
  - ò 2 x DIMM socket
  - ò Max capacity: Up to 2 GB
- € **Drive Bays:**
  - ò 2 x 3.5" HDD (Drawer)
  - ò 1 x 3.5" FDD
  - ò 1 x 5.25" slim CD-ROM (Combo for option)
- € **Audio:** AC'97 link controller
- € **Ethernet:** 10/100bps fast Ethernet controller
- € **I/O:**
  - ò 2 x Serial
  - ò 1 x Parallel
  - ò 6 x USB
  - ò 1 x RJ-45 LAN Jack
  - ò PS/2 Keyboard/mouse connector
  - ò 1 x Audio/game port



---

€ **Power Supply**

- ò Output rating: 200W~350W
- ò Input voltage: 110/230 VDC @ 47/63 Hz, (PFC optional)
- ò Output voltage: +3.3V@14A,+5V@25A,+12V @ 8A,-5V@0.5A,-12V@0.5A+5VSB@2A
- ò Safety: UL/CSA/TÜV/CE approved

€ **Cooling:**

- ò Space for 2 x 8cm system fan
- ò 2 fan for power supply

€ **Chassis Colors:** Black and beige color available, OEM color welcome

€ **Environment Specification**

- ò Operating Temperature: 0° ~ 50°C (32 ~ 113° F)
- ò Relative Humidity: 5~85%

€ **OEM Specification Welcome**

€ **Option:**

- ò Resistive touch screen
- ò 14.1"/17" TFT LCD display
- ò CD-RW & DVD Combo

€ **Dimension:**

- ò **W.430mm x H.285mm x D.175mm** (167mm including front panel)
- ò N.W. 8.5 KGS, G.W. 10KGS, CUFT.2.7